

LED Film Viewers

Salient Features

- High Power SMD LED's
- Built-in Writing Lamp(PCS & PXL models)
- Viewing Screen Adjustable Shutters
- Electronic Brightness Control
- Foot Switch Control
- Corrosion Resistant AL Body
- As per ASTM E1390



Technical Specifications:

Description	LED FV - PC	LED FV - PCS	LED FV - PXL
Viewing Area (LXW)	2.5" X 8" 60mmX200mm	4" X 12" 100mmX300mm	4.5" X 17" 110mmX425mm
Film Density	Up to 4.5 D	Up to 4.5 D	Up to 4.5 D
Uniformity Factor(g)	≥ 0.85	≥ 0.85	≥ 0.85
Input Voltage	110-260 VAC, 50 – 60Hz	110-260 VAC, 50 – 60Hz	110-260 VAC, 50 – 60Hz
Rated Output	90W	240W	320W
Surface Temp.	< 46° C	< 48° C	< 46° C
Dimension (LXWXH)	13" X 5.9" X 6.5" 330mmX150mmX 165mm	18.3" X 6.8" X 7.6" 465mmX175mmX195mm	23.4" X 6.8" X 7.6" 595mmX175mmX195mm
Housing	Powder Coated Aluminum	Powder Coated Aluminum	Powder Coated Aluminum
Max Brightness	≥ 515,000 Lux/ ≥185,000 cd/m2	≥ 500,000 Lux/ ≥180,000 cd/m2	≥ 475,000 Lux/ ≥160,000 cd/m2
Intensity Control	From 10% - 100%	From 10% - 100%	From 10% - 100%
Cooling	High capacity fans with aluminium heat sink	High capacity fans with aluminium heat sink	High capacity fans with aluminium heat sink
Weight	6.6 lbs(3 kg)	8.8 lbs(4 Kg)/12.8 lbs(5.8 Kg) with SMPS	11.6 lbs(5.3 Kg)/17.4 lbs(7.9 Kg) with SMPS

ARORA

Arora Technologies (P) Limited
 619 & 620 The Great Eastern Galleria, Plot No.20,
 Sector 4, Nerul, Navi Mumbai 400 706 India
 T: +91-22-6138 0600, 2770 3913/23, 2772 9077
 E: info@arorandt.com | W: www.arorandt.com

Authorised Reseller